


RJ Series Slim Power Relays

Key features:

- Compact and rugged power relays. Large switching capacity
- Compact housing only 12.7-mm wide.
Large contact rating
RJ1 (1-pole): 16A (UL general use rating @250V AC)
RJ2 (2-pole): 8A
- Non-polarized LED indicator available on blade type. IDEC's unique light guide structure enables high visibility of coil status from any direction.
- The smallest width for 2-pole/bifurcated contact relay
- Excellent electrical and mechanical life.
Electrical life: 200,000 operations (AC load)
Mechanical life: 30 million operations (AC coil)
- RoHS directive compliant (EU directive 2002/95/EC). Contains no lead, cadmium, mercury, hexavalent chromium, PBB or PBDE.
- Diode model:
Diode reverse withstand voltage: 1000V
- UL recognized, CSA certified, EN compliant.



UL508
UL File No. E55996



CSA C22.2 No. 14
1608322
CSA File No. LR35144




EN61810-1
VDE (REG.-Nr B312)



EN61810-1
EC Low Voltage Directive

Part Number Selection

Style	Terminal	Contact	Model	Part Number	Coil Voltage Code (Standard Stock in bold)
	Blade	SPDT	Standard	RJ1S-C-□	A24 , A110, A120 , A220, A240 , D12, D24 , D48, D100
			with LED	RJ1S-CL-□	
			with Surge Suppresion Diode	RJ1S-CD-□	D12, D24 , D48, D100
			with LED & Surge Suppresion Diode	RJ1S-CLD-□	
		DPDT	Standard	RJ2S-C-□	A24 , A110, A120 , A220, A240 , D12, D24 , D48, D100
			with LED	RJ2S-CL-□	
			with Surge Suppresion Diode	RJ2S-CD-□	D12, D24 , D48, D100
			with LED & Surge Suppresion Diode	RJ2S-CLD-□	
			Standard Bifurcated contacts (without LED indicator)	RJ22S-C-□	A12, A24 , A120 , A240 , D5, D12, D24 , D100
			Bifurcated contacts (with LED indicator)	RJ22S-CL-□	
			Bifurcated contacts diode (without LED indicator)	RJ22S-CD-□	D5, D12, D24 , D48, D100
			Bifurcated contacts diode (with LED indicator)	RJ22S-CLD-□	
	PCB	SPDT	Standard	RJ1V-C-□	
			High Capacity	RJ1V-CH-□	
		SPST-NO	Standard	RJ1V-A-□	A24 , A110, A120 , A220, A240 , D5, D6, D12, D24 , D48, D100
			High Capacity	RJ1V-AH-□	
		DPDT	Standard	RJ2V-C-□	
		DPST-NO	Standard	RJ2V-A-□	
		DPDT	Bifurcated contacts	RJ22V-C-□	A12, A24 , A120 , A240 , D5, D12, D24 , D48, D100
		DPST-NO	Bifurcated contacts	RJ22V-A-□	

Ordering Information

When ordering, specify the Part No. and coil voltage code:

(example) **RJ1S-C-** **A120**
Part No. Coil Voltage Code

Coil Voltage Table

Coil Voltage Code	A12	A24	A110	A120	A220	A240	D5	D6	D12	D24	D48	D100
Coil Rating	12V AC	24V AC	110V AC	120V AC	220V AC	240V AC	5V DC	6V DC	12V DC	24V DC	48V DC	100-110V DC

Sockets

Relays		Standard DIN Rail Mount	Finger-safe DIN Rail Mount	PCB Mount
Blade Models	RJ1S (Std)	SJ1S-05BW	SJ1S-07LW	SJ1S-61
	RJ2S (Std)/RJ22S	SJ2S-05BW	SJ2S-07LW	SJ2S-61
PCB Models	RJ1V (Std)	—	SQ1V-07B*	SQ1V-63*
	RJ1V (HC) RJ2V/RJ22V	—	SQ2V-07B*	SQ2V-63*
		 Shown with optional marking plate.		



*Hold-down clip or spring must be removed to use with RJ PCB relays.

Replacement Hold Down Springs

Part Number	Used With Socket
SJ9Z-CM	SJ1S-05BW, SJ1S-07LW, SJ2S-05BW, SJ2S-07LW
SQ9Z-C	SQ1V-07B, SQ2V-07B
SQ9Z-C63	SQ1V-63, SQ2V-63

Jumpers for SJ Sockets

Poles	Part Number	Quantity
2	SJ9Z-JF2	Must purchase in quantities of 10.
5	SJ9Z-JF5	
8	SJ9Z-JF8	
10	SJ9Z-JF10	

Accessories

Item	Appearance	Use with	Part No.	Remarks
Aluminum DIN Rail (1 meter length)		All DIN rail sockets	BNDN1000	The BNDN1000 is designed to accommodate DIN mount sockets. Made of durable extruded aluminum, the BNDN1000 measures 0.413 (10.5mm) in height and 1.37 (35mm) in width (DIN standard). Standard length is 39" (1,000mm).
DIN Rail End Stop		DIN rail	BNL5	9.1 mm wide.
Marking Plate		Finger safe sockets (ONLY)	SJ9Z-PWPN10	10 pieces per pack

Specifications

Model		RJ1	RJ2	RJ22S	RJ22V
Number of Poles		1-pole	2-pole		
Contact Configuration		SPDT	DPDT	DPDT bifurcated contacts	DPDT (bifurcated), DPST-NO (bifurcated)
Contact Material		Silver-nickel alloy		AgNi (gold clad)	
Degree of Protection		IP40			Flux-tight structure
Contact Resistance (initial value) ¹		50 mΩ maximum			
Operating Time ²		15ms maximum (with diode: 20 ms maximum)			
Release Time ²		10 ms maximum (with diode: 20 ms maximum)			
Dielectric Strength	Between contact and coil	5000V AC, 1 minute			
	Between contacts of the same pole	1000V AC, 1 minute			
	Between contacts of different poles	—	3000V AC, 1 minute		
Vibration Resistance	Operating extremes	10 to 55 Hz, amplitude 0.75 mm			
	Damage limits	10 to 55 Hz, amplitude 0.75 mm			
Shock Resistance	Operating extremes	NO contact: 200 m/s ² , NC contact: 100 m/s ²			
	Damage limits	1000 m/s ²			
Electrical Life (rated load)		AC load: 200,000 operations minimum (operation frequency 1800 operations per hour) DC load: 100,000 operations minimum (operation frequency 1800 operations per hour)		AC load: 100,000 operations minimum (operation frequency 1,800 per hour) DC load: 200,000 operations minimum (operation frequency 1,800 per hour)	
Mechanical Life (no load)		AC coil: 30,000,000 operations minimum (operation frequency 18,000 operations per hour) DC coil: 50,000,000 operations minimum (operation frequency 18,000 operations per hour)		AC load: 10 million operations minimum (operating frequency 18,000 operations per hour) DC load: 20 million operations minimum (operating frequency 18,000 operations per hour)	
Operating Temperature ³		−40 to +70°C (no freezing)			
Operating Humidity		5 to 85% RH (no condensation)			
Weight (approx.)		19g (blade type), 17g (PCB form C type), 16g (PCB form A type)		19g	DPDT: 17g, DPST-NO: 16g



Note: Above values are initial values.

1. Measured using 5V DC, 1A voltage drop method.

2. Measured at the rated voltage (at 20°C), excluding contact bounce time.

3. 100% rated voltage.

Switches & Pilot Lights

Signaling Lights

Relays & Sockets

Timers

Contactors

Terminal Blocks

Circuit Breakers

Coil Ratings

Rated Voltage			Coil Voltage Code	Rated Current (mA) ±15% (at 20°C)				Coil Resistance (ohms)±10% (at 20°C)	Operating Characteristics²			Power Consumption	
				Without LED¹		With LED¹			Pickup Voltage	Dropout Voltage	Maximum Allowable Voltage³		
				50Hz	60Hz	50Hz	60Hz						
AC	Blade & PCB Models	24V	A24	43.9	37.5	47.5	41.1	243	80% max	30% min	140%	0.9VA (60Hz)	
		120V	A120	8.8	7.5	8.7	7.4	6,400					
		240V	A240	4.3	3.7	4.3	3.7	25,570					
	Bifurcated Models	12V	A12	87.3	75.0	91.1	78.8	62.5				Approx. 1.1VA (50Hz) 0.9 to 1.2VA (60Hz)	
		24V	A24	43.9	37.5	47.5	41.1	243					
		120V	A120	8.8	7.5	8.7	7.4	6,400					
		240V	A240	4.3	3.7	4.3	3.7	25,570					
Rated Voltage			Coil Voltage Code	Rated Current (mA) ±15% (at 20°C)				Coil Resistance (ohms)±10% (at 20°C)	Operating Characteristics²			Power Consumption	
				Without LED¹		With LED¹			Pickup Voltage	Dropout Voltage	Maximum Allowable Voltage³		
DC	Blade Models	12V	D12	44.2		48.0		271	70% max	10% min	170%	0.53W	
		24V	D24	22.1		25.7		1,080			160%		
		48V	D48	11.0		10.7		4,340					
		100-110V	D100	5.3 - 5.8		5.2 - 5.7		18,870					
	PCB Models	5V	D5	106		—		47.2	70% max	10% min	170%	0.53-0.64W	
		6V	D6	88.3		—		67.9					
		12V	D12	44.2		—		271					
		24V	D24	22.1		—		1,080			160%		
		48V	D48	11.0		—		4,340					
		100-110V	D100	5.3 - 5.8		—		18,870					
		5V	D5	106		110		47.2			170%		
	Bifurcated Models	12V	D12	44.2		48.0		271	70% max	10% min	170%	Approx. 0.53 to 0.64W	
		24V	D24	22.1		25.7		1,080					
		48V	D48	11		10.7		4,340					
		100-110V	D100	5.3-5.8		5.2-5.7		18,870			160%		



1. LED Indicator is only available on Blade or Bifurcated relays.
2. Operating characteristics are at 20°C.
3. The maximum allowable voltage is the maximum value which can be applied to the relay coils.

Contact Ratings

Model		Contact	Allowable Contact Power		Rated Load			Allowable Switching Current	Allowable Switching Voltage	Minimum Applicable Load	
			Resistive Load	Inductive Load	Voltage	Resistive Load	Inductive Load cosφ=0.3 L/R=7ms				
Blade Models	1 pole	NO	3000VA	1875VA	250V AC	12A	7.5A	16A	AC250V DC30V	DC5V 100mA	
		NC	3000VA	1875VA	250V AC	12A	7.5A	6A			
	2 poles	NO	2000VA	1000VA	250V AC	8A	4A	4A	AC250V DC30V	DC5V 10mA	
		NC	2000VA	1000VA	250V AC	8A	4A	4A			
	2 poles (bifurcated contacts)	NO	250VA AC 30W DC	100VA AC 15W DC	250V AC 30V DC	1A 1A	0.4A 0.5A	1A	250V AC 125V DC	1V DC 100μA	
		NC	250VA AC 30W DC	100VA AC 15W DC	250V AC 30V DC	1A 1A	0.4A 0.5A				
PCB Models	1 pole	Standard Type	NO	3000VA	1875VA	250V AC	12A	7.5A	12A	AC250V DC125V	DC5V 100mA
				360W	180W	30V DC	12A	6A			
			NC	3000VA	1875VA	250V AC	12A	7.5A	6A		
				180W	90W	30V DC	6A	3A			
		High Capacity Type	NO	4000VA	2000VA	250V AC	16A	8A	16A	AC250V DC125V	DC5V 100mA
				480W	240W	30V DC	16A	8A			
			NC	4000VA	2000VA	250V AC	16A	8A	8A		
				240W	120W	30V DC	8A	4A			
	2 poles	NO	2000VA	1000VA	250V AC	8A	4A	8A	AC250V DC125V	DC5V 10mA	
			240W	120W	30V DC	8A	4A				
			NC	2000VA	1000VA	250V AC	8A	4A			4A
				120W	60W	30V DC	4A	2A			
		2 poles (bifurcated contacts)	NO	250VA AC 30W DC	100VA AC 15W DC	250V AC 30V DC	1A 1A	0.4A 0.5A	1A	250V AC 125V DC	1V DC 100μA
			NC	250VA AC 30W DC	100VA AC 15W DC	250V AC 30V DC	1A 1A	0.4A 0.5A			

Agency Ratings

Voltage	UL							
	General Use						Resistive	
	RJ1		RJ2		RJ22		RJ22	
	NO	NC	NO	NC	NO	NC	NO	NC
250V AC	16A	6A	8A	4A	1A	1A	—	—
30V DC	12A	6A	8A	4A	—	—	1A	1A

Voltage	CSA													
	General Use		Resistive						Inductive					
	RJ22		RJ1		RJ2		RJ22		RJ1		RJ2		RJ22	
	NO	NC	NO	NC	NO	NC	NO	NC	NO	NC	NO	NC	NO	NC
250V AC	1A	1A	12A	12A	8A	8A	—	—	7.5A	7.5A	4A	4A	—	—
30V DC	—	—	12A	6A	8A	4A	1A	1A	6A	3A	4A	2A	1A	1A

Voltage	VDE					
	Resistive				AC-15, DC-13*	
	RJ1	RJ2	RJ22		RJ1	RJ2
	NO	NO	NO	NC	NO	NO
250V AC	12A	8A	1A	1A	6A	3A
30V DC	12A	8A	1A	1A	2.5A	2A



*According to the utilization categories of IEC60947-5-1

Socket Specifications

	Socket	Terminal	Electrical Rating	Wire Size	Torque
DIN Rail/ Panel Mount	SJ1S-05BW	M3 screw with captive wire clamp	250V, 12A	Maximum up to 2 - #14 AWG	0.6 - 1.0N•m (Maximum 1.2N•m)
	SJ2S-05BW	M3 screw with captive wire clamp	250V, 8A	Maximum up to 2 - #14 AWG	0.6 - 1.0N•m (Maximum 1.2N•m)
Finger-safe DIN Rail/Panel Mount	SJ1S-07LW	M3 screw with captive wire clamp, fingersafe	250V, 12A	Maximum up to 2 - #14 AWG	0.6 - 1.0N•m (Maximum 1.2N•m)
	SJ2S-07LW	M3 screw with captive wire clamp, fingersafe	250V, 8A	Maximum up to 2 - #14 AWG	0.6 - 1.0N•m (Maximum 1.2N•m)
	SQ1V-07B	M3 screw with box clamp, fingersafe	300V, 12A	Maximum up to 2 - #14 AWG	1.0N•m Maximum
	SQ2V-07B	M3 screw with box clamp, fingersafe	300V, 10A	Maximum up to 2 - #14 AWG	1.0N•m Maximum
PCB Mount	SJ1S-61	PCB mount	250V, 12A	—	—
	SJ2S-61	PCB mount	250V, 8A	—	—
	SQ1V-63	PCB mount	300V, 12A	—	—
	SQ2V-63	PCB mount	300V, 12A	—	—

Switches & Pilot Lights

Signaling Lights

Relays & Sockets

Timers


Contactors

Terminal Blocks


Circuit Breakers

Electrical Life Curve (Resistive Load)


RJ1



RJ1 High Capacity




RJ2




Maximum Switching Capacity (Resistive Load)


RJ1



RJ1 High Capacity




RJ2




Operating Temperature and Coil Temperature Rise


RJ1 (AC Coil, 60 Hz)




RJ1 (AC Coil, 50 Hz)




RJ1 (DC Coil)




RJ2 (AC Coil, 60 Hz)




RJ2 (AC Coil, 50 Hz)




RJ2 (DC Coil)




RJ22 (AC Coil, 60 Hz)



RJ22 (AC Coil, 50 Hz)




RJ22 (DC Coil)




The above temperature rise curves show characteristics when 100% the rated coil voltage is applied.
The slanted dashed line indicates allowable temperature rise for the coil at different ambient temperatures.

Internal Connection (View from Bottom)


RJ1-C-* Standard



RJ1-CL-* With LED Indicator




Coil voltage 24V AC/DC and below




Coil voltage greater than 24V AC/DC


RJ1-CD-* With Diode



RJ1-CLD-* With LED Indicator and Diode




Coil voltage 24V DC and below




Coil voltage greater than 24V DC

RJ2-C/RJ22-C-* Standard




RJ2-CL/RJ22-CL-* With LED Indicator




Coil voltage 24V AC/DC and below

RJ22V-A-*




Coil voltage greater than 24V AC/DC


RJ2-CD-/RJ22-CD-* With Diode



RJ2-CLD-/RJ22-CLD-* With LED Indicator and Diode



Coil voltage 24V DC and below




Coil voltage greater than 24V DC


Dimensions (mm)

Blade Relay (mm)

RJ1S




RJ2S/RJ22S




All dimensions in mm.

PCB Relay (mm)


RJ1V-C-*




RJ1V-A-*




RJ1V-CH-*/RJ2V-C-*




RJ1V-AH-*/RJ2V-A-*



RJ22V-C-*




RJ22V-A-*




Dimensions con't (mm)

Standard DIN Rail Mount Sockets

SJ1S-05BW




SJ2S-05BW




Finger-safe DIN Rail Mount Sockets


SJ1S-07LW




SJ2S-07LW



SQ1V-07B




SQ2V-07B




Dimensions con't (mm)

PC Mount Sockets


SJ1S-61



SJ2S-61



SQ1V-63



SQ2V-63

